

Heavy Duty T-Bolt Clamps

C



Style TBC - 3/4" wide 300 series stainless steel band, .025" thick. Opens 3/32" above and tightens 7/32" smaller than normal I.D. for a total of 5/16" range. **Alloy steel bolt.** Packed 10 per box.



Style STBC - 3/4" wide 300 series stainless steel band, .025" thick. Opens 3/32" above and tightens 7/32" smaller than nominal I.D. for a total of 5/16" range. **300 series stainless steel bolt.** Packed 10 per box.

T-BOLT CLAMPS

PART NO.	SIZE	O.D. RANGE (MM)		TORQUE IN/LBS
		FROM	TO	
TBC150	1 1/2"	32.5	40.8	70
TBC175	1 3/4"	38.8	46.8	70
TBC188	1 7/8"	42.6	50.0	70
TBC200	2"	45.2	53.1	70
TBC225	2 1/4"	51.5	59.5	70
TBC238	2 3/8"	54.0	62.7	70
TBC250	2 1/2"	57.9	65.8	70
TBC256	2 9/16"	59.5	67.4	70
TBC263	2 5/8"	61.1	69.0	70
TBC275	2 3/4"	64.2	72.2	70
TBC288	2 7/8"	67.4	75.4	70
TBC300	3"	70.6	78.5	70
TBC312	3 1/8"	73.8	81.7	70
TBC325	3 1/4"	76.9	84.9	70
TBC350	3 1/2"	83.3	91.2	70
TBC375	3 3/4"	89.6	97.6	70
TBC400	4"	96.0	103.9	70
TBC425	4 1/4"	102.3	110.3	70
TBC450	4 1/2"	108.7	116.6	70
TBC475	4 3/4"	115.0	123.0	70
TBC500	5"	121.4	129.3	70
TBC525	5 1/4"	127.7	135.0	70
TBC550	5 1/2"	134.0	142.0	70
TBC575	5 3/4"	140.4	148.4	70
TBC600	6"	146.8	154.7	70
TBC625	6 1/4"	153.0	161.0	70
TBC650	6 1/2"	159.5	167.4	70
TBC675	6 3/4"	165.0	173.0	70
TBC700	7"	172.2	180.0	70
TBC750	7 1/2"	184.0	192.0	70
STBC150	1 1/2"	32.5	40.8	50
STBC175	1 3/4"	38.8	46.8	50
STBC188	1 7/8"	42.6	50.0	50
STBC200	2"	45.2	53.1	50
STBC225	2 1/4"	51.5	59.5	50
STBC238	2 3/8"	54.0	62.7	50
STBC250	2 1/2"	57.9	65.8	50
STBC256	2 9/16"	59.5	67.4	50
STBC263	2 5/8"	61.1	69.0	50
STBC275	2 3/4"	64.2	72.2	50
STBC288	2 7/8"	67.4	75.4	50
STBC300	3"	70.6	78.5	50
STBC312	3 1/8"	73.8	81.7	50
STBC325	3 1/4"	76.9	84.9	50
STBC350	3 1/2"	83.3	91.2	50
STBC375	3 3/4"	89.6	97.6	50
STBC400	4"	96.0	103.9	50
STBC425	4 1/4"	102.3	110.3	50
STBC450	4 1/2"	108.7	116.6	50
STBC475	4 3/4"	115.0	123.0	50
STBC500	5"	121.4	129.3	50
STBC525	5 1/4"	127.7	135.0	50
STBC550	5 1/2"	134.0	142.0	50
STBC575	5 3/4"	140.4	148.4	50
STBC600	6"	146.8	154.7	50
STBC625	6 1/4"	153.0	161.0	50
STBC650	6 1/2"	159.5	167.4	50
STBC675	6 3/4"	165.0	173.0	50
STBC700	7"	172.2	180.0	50
STBC750	7 1/2"	184.0	192.0	50